



Elastotex Textured Finish TECHNICAL DATA SHEET

DESCRIPTION



Elastotex is a moderately flexible textured coating based on waterborne styrene acrylic copolymer, ideal for transforming interior and exterior surfaces with stone-like finish. Available in 4 grades – Superfine, Fine, Medium and Coarse.

COLOUR RANGE

Natural; Can also be tinted to a wide range of colours

FEATURES

- Excellent coverage
- Flexible coating – will bridge over small cracks and movable construction joints
- Provides an even finish over minor surface imperfections
- Mildew and water resistant
- Easy to apply using trowel or spray gun (should be applied by a professional)
- Can be custom tinted

SPREAD RATE

Superfine – 1.2kg/m² (2.5 lb per square yard) *

Fine – 1.6kg/m² (3.5 lb per square yard)

Medium – 2.0kg/m² (4.5 lb per square yard)

Coarse - 2.4kg/m² (5.5 lb per square yard)

Number of Coats: 1

*Under some conditions, 2 coats of Superfine may be required for best results.

DIRECTIONS FOR USE

Elastotex Textured Finish may be applied by experienced personnel using trowels or specialised spraying equipment. Elastotex Textured Finish will adhere to sound, dust- and mildew-free blockwork, plaster, hardboard or wood and cement boards. On wood and porous substrates, use of an appropriate primer is recommended. On concrete and cement substrates, Elastotex Textured Finish may be applied directly to the bare surface, but the finish, appearance and durability may be enhanced by the application of an appropriate primer or basecoat. Elastotex Textured Finish is supplied in a consistency ready for use and should need no thinning. Mix thoroughly before use and thin sparingly with water only if necessary, to ease application.



Below is recommendation for spray application:

Material	Nozzle Size	Sprayers
Elastotex Coarse	6 mm or 8 mm nozzle	Graco RTX1500 or HTX 2030 or equivalent equipment
Elastotex Medium	6 mm or 8 mm nozzle	Graco RTX 1500 or HTX 2030 or equivalent equipment
Elastotex Fine	6 mm nozzle	Graco RTX 1500 or HTX 2030 or equivalent equipment
Elastotex Extra Fine	6 mm nozzle	Graco RTX 1500 of HTX 2030 or equivalent equipment

STORAGE LIFE

Minimum 18 months. Best to use as soon as possible after purchase. We recommend that Elastotex Textured Finish should be stored in a cool place away from direct sunlight.

DRYING TIME

Touch dry: 1-2 hours depending upon atmospheric conditions Recoat: NA Curing time: 1 - 3 days dependent upon conditions

CLEAN- UP

Clean tools and equipment with water after use

COMPOSITION

Titanium dioxide, calcium carbonate, calcined clay, mica, organic biocides, styrene acrylic copolymer, cellulose fibres.

PRODUCT CHARACTERISTICS

Colour & Form	Cream coloured paste, Custom colours
Solids Content	83 -85%
Weight per gallon (US)	Approximately 15 lb (6.8kg)
Gloss at 60°	Matt
Drying Time	Touch dry in 1-2 hours, but may be extended depending upon coating thickness and atmospheric conditions
Thinner	Water
Pot Life	Not applicable. Single component

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

SAFETY DIRECTIONS

NON- FLAMMABLE. Store in a cool place. Non- toxic under normal conditions.

FIRST AID: In case of skin contact, wash thoroughly with soap and water. If product comes into contact with eyes, flush immediately with plenty water and seek medical advice. **DO NOT SWALLOW.** If ingested seek medical advice immediately.

TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.